


esscobathware.com Document No. SNW/ECS/24/355PNPP











General Information	
Product Code	ECS-WHT-355PNPP
Brand	Essco
Colour	White
Туре	Anglo Indian-WC (P trap)
Material	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	475x570x400 mm
Bowl Opening (Inner Dimension)	375x230 mm
Product Net Weight	19.5 kg
Product Gross Weight	22.7 kg
Packaging Dimension	585x490x455 mm
Outlet	Vertical
Trap Distance	P-Trap - 180 mm
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole dia. \emptyset 50 \pm 3 mm
	External diameter of outlet hole dia. Ø 100 ± 5 mm
	Vertical distance between the Floor and the centre line of the inlet hole ≤ 355 mm
Product Features	Packed with Accessories Completet Trap galze, Dual Flushing - 3/6 LPF Anti germ glaze.
ACCESSORIES INCLUDED	
PP close seat cover	ECS-WHT-107N
Floor fixing screw	ZPS-SNS-FB01
ACCESSORIES RECOMMENDATION	
Wall Hung Cistern	WHE-WHT-183L
CARL AND CLEANING CHIRELINES	

CARE AND CLEANING GUIDELINES

¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.

- The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ¬ Carefully inspect the new product for damage before installation.
- \neg Risk of external leakage. Do not lift or rock the bowl after placement.
- \neg Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \neg Do not allow cleaners to sit or soak on the product.
- $_{
 eg}$ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- \neg Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001





DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product