


esscobathware.com Document No. SNW/ECS/24/553SSPP











General Information	
Product Code	ECS-WHT-553SSPP
Brand	Essco
Colour	White
Туре	EWC S-Trap
Material	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	350x530x400 mm
Bowl Opening (Inner Dimension)	270x355 mm
Product Net Weight	13.0 Kg
Product Gross Weight	16.5 Kg
Packaging Dimension	555x405x410 mm
Outlet	Vertical
Trap Distance	S Trap
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole dia. Ø 57 ± 3 mm
	External diameter of outlet hole dia. \emptyset 100 \pm 5 mm
	Horizontal distance between the WC edge and the centre line of the waste outlet hole ≤ 105 mm
Product Features	Elegant Design with Concealed trap Complete Trap Wash PP Soft Close seat cover Water Usage- Dual Flushing - 3/6 LPF (Wash Down Flushing) Smooth Glaze Surface Material - Vitreous China (VC) Product With Complete Genuine Fixing Accessories
ACCESSORIES INCLUDED	
Seat Cover	ECS-WHT-109S
Floor fixing screw	ZPS-SNS-FB01
Inlet Outlet Gasket	ZPS-BLK-GK02
ACCESSORIES RECOMMENDATION	
Wall Hung Cistern	ESH-WHT-184N,ESH-WHT-184NL,ESH-WHT-184NT,ESH-WHT-184AN, ESH-WHT-184ANL,ESH-WHT-184ANT,ESH-WHT-184NBTT,ESH-WHT-184NBTL
CARE AND CLEANING GUIDELINES	

- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use
- \neg The product is heavy and it is recommended that two persons hold it while it is being fixed.
- Carefully inspect the new product for damage before installation.
- ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ¬ Risk of external leakage. Do not lift or rock the bowl after placement.
- ¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ¬ Do not allow cleaners to sit or soak on the product.
- n Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ¬ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001





DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product