

esscobathware.com Document No. SNW/ECS/24/851S300SPPSM









ECS-WHT-851S300SPPSM
Essco
White
Single piece-WC (S trap)
Ceramic-Vitreous China (VC)
360x705x705 mm
265x330 mm
41.5 kg
43.5 kg
415X380X735 mm
Vertical
S Trap
External diameter of outlet hole dia. Ø 80 mm
Horizontal distance between the wall line and the centre line of the waste outlet hole ≤ 300 mm
Syphonic WC,Trap Glaze, Packed with Accessories PP Slim Seat cover with Accessories Dual Flushing - 2/6 & 4/6 LPF, Anti germ glaze. Material - Vitreous China (VC)
ECS-WHT-113SPP
ZPS-SNS-FB01
ZCF-WHT-FT013
ZPS-WHT-1401

CARE AND CLEANING GUIDELINES

- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- Carefully inspect the new product for damage before installation.
- ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ¬ Risk of external leakage. Do not lift or rock the bowl after placement.
- → Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \neg Do not allow cleaners to sit or soak on the product.
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ¬ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- \neg Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001





DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product

Prepared by Checked by Approved by